

NI-BASE ALLOYS

Application Segments

Aerospace	Automotive	Oil & Gas / CPI	Land Based Turbines
-----------	------------	-----------------	---------------------

Available Product Variants

Long Products* | Semi-Finished Products / Billet | Plates | Open Die Forgings

Product Description

BÖHLER L718AMS is a corrosion and heat resistant nickel alloy - precipitation hardenable - in the form of bars, forging and forging stock. High resistance to creep and stress-rupture up to 1300°F (704°C) and oxidation resistance up to 1800°F (982°C). High duty parts and components for oil & gas and CPI applications, components for automotive, gas turbines, aerospace engines, high-speed airframe parts such as disks, buckets, spacers and high temperature bolts and fasteners.

Process Melting

VIM + VAR

Applications

- > Other Aerospace Components
- > Blades & Shafts for Turbines and Compressors
- Components for Industrial Gas Compressors
- > Drilling tools and components
- > Power Generation (Gas/Steam/ Nuclear)
- > Well Completion Tools
- > Automotive

- > Turbine and Engine Parts (Aerospace)
- > Chemical industry general
- > Components for underground construction (drilling, shafts, etc.)
- > Fasteners, Bolts, Nuts
- > Other Power Generation Components
- > Well Logging Tools
- > Motorsport industry

- > Aerospace
- > Components for Chemical plants (incl. LNG, FGD, Urea, LDPE, etc.)
- > CPI (incl. LNG, Urea)
- > Paper and Pulp Industry / Printing
- > Other Oil and Gas + CPI components
- Wellhead, X-mas trees and Manifolds (incl. Tubing hangers), BOPs

Technical data

Material designation	
Alloy 718	Market grade
2.4668	SEL
NiCr19NbMo/ NiCr19Fe19Nb5Mo3	EN
NC19FCNb	
N07718	UNS

Standards		
	B637	ASTM
	5662 5663	AMS



^{*} Presented data refer exclusively to long products. Please observe the detailed explanations at the end of the data sheet (pdf).



Chemical composition (wt. %)

С	Si	Mn	P	S	Cr	Мо	Ni	Cu	Со	Ti	Al	Nb	В	Fe	Pb	Bi	Se
max 0.08		max. 0.35	max. 0.015	max. 0.015	17.00 to 21.00	2.80 to 3.30	50.00 to 55.00	max. 0.30	max. 1.00	0.65 to 1.15		4.75 to 5.50	max. 0.006	REM	max. 5ppm	max. 0.3ppm	max. 3ppm

Related to AMS5662

Delivery condition

Solution annealed

Haraness (HB) max. 2// bars and forging stock, max 254 mm diameter	Hardness (HB)	max. 277 bars and forging stock, max 254 mm diameter
--	---------------	--

Round Bars and Wire Rod (if any)

Die	amet		MOQ ex mill	Length m			Tolerance
	mm		kg ROL	LED	m		
5.00	T-1	13.50	-		T-		
12.50	-	55.00	600	3.00	-	4.00	IT h/k 12
55.01	1-1	101.60	2,550	3.00	-	4.00	IT h/k 12
			FOR	GED			
101.61	T-1	254.00	2,200	2.00	T-	6.00	IT h/k 12

^{*} Diameter 5.00 - 13.50 mm available as Wire Rod.

Diameter 12.5 - 101.6 mm round bars.

More information regarding MOQ and tolerances for Wire Rod products upon request.

If other available product variants are listed in addition to long products, please note that these may differ in terms of melting process, technical data, delivery and surface condition as well as available product dimensions. For mandatory technical specifications, other requirements and dimensions, please contact our regional voestalpine BÖHLER sales companies. The data contained in this brochure is merely for general information and therefore shall not be binding on the company. We may be bound only through a contract explicitly stipulating such data as binding. Measurement data are laboratory values and can deviate from practical analyses. The manufacture of our products does not involve the use of substances detrimental to health or to the ozone layer.

voestalpine BÖHLER Edelstahl GmbH & Co KG

Mariazeller Straße 25 8605 Kapfenberg, AT T. +43/50304/20-0 E. info@bohler-edelstahl.at https://www.voestalpine.com/bohler-edelstahl/de/

