

CORROSION RESISTANT STEELS - MARTENSITIC PRECIPITATION HARDENING (PH) STEELS

Application Segme	1115			
Aerospace	Engineerin	g		
Available Product \	/ariants			
Long Products*	Semi-Finished P	roducts / Billet	Plates]
* Presented data refer ex	clusively to long prod	ucts. Please observe the	detailed explanati	ons at the end of the data sheet (pdf).
Product Description	1			
BÖHLER N701 AMS is a thicknesses up to 203 mr	premium, aerospace n in the solution-anne	-quality corrosion-resistan ealed condition, as well as	t steel available ir pre-forging stock	n bars, wire, and forgings with diameters/ of any size.
It is a martensitic, precipi be achieved through cold	tation-hardenable chr working and subseq	omium-nickel-copper stee uent precipitation hardenii	el with high streng	th and toughness. Further strength increases can
These products are typicatoughness and strength in	ally used for parts req n large dimensions. H	uiring corrosion resistanc lowever, their use is not lii	e and high streng mited to such app	th up to 316 °C and must exhibit good transverse lications.
Certain processing metho	ods and operating cor	nditions can make these p	roducts susceptib	ole to stress corrosion cracking.
Process Melting				
Airmelted + VAR				
Applications				
> Aerospace	> Other Aerospac	e Components	>	Structural parts (Aerospace)
Technical data				
Material designation		Standards		
15-5 PH	Market grade	A564	ASTM	_
1.4545	SEL	5659	AMS	-
X5CrNiCu15-5	EN			

S15500 UNS



CORROSION RESISTANT STEELS - MARTENSITIC PRECIPITATION HARDENING (PH) STEELS

BÖHLER N701AMS

Chemical composition (wt. %)

С	Si	Mn	Р	S	Cr	Мо	Ni	Cu	Nb
max. 0.07	max. 1.00	max. 1.00	max. 0.030	max. 0.015	14.00 to 15.50	max. 0.50	3.50 to 5.50	2.50 to 4.50	5xC to 0.45

Related to AMS 5659 type 1

Delivery condition

Solution annealed							
Hardness (HB)	max. 363 bars, hot or cold finished, forgings						
Tensile Strength (MPa)	max. 1,207 for wire products						

Round Bars and Wire Rod (if any)

Diameter			MOQ ex mill	L	eng	jth	Tolerance		
	mn	n	kg	m					
	ROLLED								
5.01	T-	12.49	1,100	3.00 - 4.00			IT h/k 11		
12.50	-	55.00	1,200	3.00	-	4.00	IT h/k 11		
55.01	-	120.00	2,300	3.00 -		4.00	IT h/k 11		
120.01	-	140.00	2,300	3.00 - 5.00		5.00	IT h/k 14		
FORGED									
140.01	-	203.20	2,350	2.00 -		5.00	IT h/k 14		
203.21	-	304.80	3,500	2.00 -		5.00	IT h/k 14		

Flat Bars

Width Thickness mm mm			MOQ ex mill kg	Le	enç m	ŋth	Tolerance			
	ROLLED									
15.00	-	121.00	8.00	-	86.00	1,300	3.00	-	4.00	LN 1017
120.00	-	150.00	25.00	-	85.00	2,550	3.00	-	4.00	LN 1017
150.00	-	275.00	20.00	-	100.00	2,550	3.00	-	4.00	LN 1017
275.00	-	330.00	25.00	-	80.00	2,550	3.00	-	4.00	LN 1017

If other available product variants are listed in addition to long products, please note that these may differ in terms of melting process, technical data, delivery and surface condition as well as available product dimensions. For mandatory technical specifications, other requirements and dimensions, please contact our regional voestalpine BÖHLER sales companies. The data contained in this brochure is merely for general information and therefore shall not be binding on the company. We may be bound only through a contract explicitly stipulating such data as binding. Measurement data are laboratory values and can deviate from practical analyses. The manufacture of our products does not involve the use of substances detrimental to health or to the ozone layer.

voestalpine BÖHLER Edelstahl GmbH & Co KG

Mariazeller Straße 25 8605 Kapfenberg, AT T. +43/50304/20-0

1. +43/30304/20-0

 $\hbox{E. info@bohler-edelstahl.at}\\$

https://www.voestalpine.com/bohler-edelstahl/de/

