

# ENGINEERING STEELS - HEAT TREATABLE AND NITRIDING STEELS

# **Application Segments**

$\Delta \rho$	rospac	Α.

#### **Available Product Variants**

Long Products

## **Product Description**

BÖHLER V354 is an alloyed Cr-Mo-V quenched and tempered steel for high strength and high temperature requirements, good weldability and suitable for nitriding. Insensitive to tempering embrittlement due to Mo content.

Mainly for components in the aerospace industry to be welded and nitrided with high quenched and tempered strength, at operating temperatures from  $-75^{\circ}$  C to  $500^{\circ}$  C.

#### **Process Melting**

Airmelted

### **Applications**

> Structural parts (Aerospace)

> Other Aerospace Components

> Aerospace

#### Technical data

Material designation		Standards	
1.7734	Market avade	1.7734	WL
15CDV6	Market grade		
1.7734	SEL		

# Chemical composition (wt. %)

С	Si	Mn	P	S	Cr	Мо	V
0.12 to 0.18	max. 0.20	0.80 to 1.10	max. 0.020	max. 0.015	1.25 to 1.50	0.80 to 1.00	0.20 to 0.30

Related to WL 1.7734





# ENGINEERING STEELS - HEAT TREATABLE AND NITRIDING STEELS

#### **Delivery condition**

Annealed					
Hardness (HB)	max. 197   Bars from 5 to 250 mm diameter				
Hardened and Tempered					
Tensile Strength (MPa)	min. 700   from 5 to 250 mm diameter				
Yield Strength (MPa)	min. 550   from 5 to 250 mm diameter				
Hardened and Tempered Tensile Strength (MPa)	980 to 1,180   from 5 to 100 mm diameter				
· · · · · · · · · · · · · · · · · · ·	980 to 1,180   from 5 to 100 mm diameter min. 790   from 5 to 100 mm diameter				
Tensile Strength (MPa)					
Tensile Strength (MPa) Yield Strength (MPa)					

#### Round Bars and Wire Rod (if any)

Diameter		ter MOQ ex mill Length		Length		Tolerance	
mm			kg		kg m		
ROLLED							
5.01	-	12.49	850	3.00	-	4.00	IT h/k 11
12.50	-	55.00	1,000	3.00	-	4.00	IT h/k 11
55.01	-	69.00	1,200	3.00	-	4.00	IT h/k 11
69.01	-	72.00	1,000	3.00	-	4.00	IT h/k 11
72.01	-	82.00	1,150	3.00	-	4.00	IT h/k 11
82.01	-	120.00	1,400	3.00	-	4.00	IT h/k 11
120.01	-	150.00	1,400	3.00	-	5.00	IT h/k 14
	- ' - '		FC	ORGED			
150.01	-	152.00	1,200	2.00	-	5.00	IT h/k 14
152.01	-	192.00	950	2.00	-	5.00	IT h/k 14
192.01	1-	203.20	1,440	2.00	-	5.00	IT h/k 14

If other available product variants are listed in addition to long products, please note that these may differ in terms of melting process, technical data, delivery and surface condition as well as available product dimensions. For mandatory technical specifications, other requirements and dimensions, please contact our regional voestalpine BÖHLER sales companies. The data contained in this brochure is merely for general information and therefore shall not be binding on the company. We may be bound only through a contract explicitly stipulating such data as binding. Measurement data are laboratory values and can deviate from practical analyses. The manufacture of our products does not involve the use of substances detrimental to health or to the ozone layer.

#### voestalpine BÖHLER Edelstahl GmbH & Co KG

Mariazeller Straße 25 8605 Kapfenberg, AT T. +43/50304/20-0 E. info@bohler-edelstahl.at https://www.voestalpine.com/bohler-edelstahl/de/

